

Plus Touch

PSS-023-Plus_Touch-01

Plus Touch can monitor temperature, humidity, ammonia, carbon dioxide, and more. It can then use those conditions to influence how it controls equipment.



BENEFITS

- Easy set up and management with intuitive user experience, on-board diagnostics, and self-tests, with the entire system updatable from USB

FEATURES

- Completely programmable in five minutes
- Monitors humidity, ammonia, carbon dioxide and more with optional sensors
- Can run variable frequency drives (VFDs), single stage fans, and soaking systems from one interface
- Two variable AC stages
- 30ft. temperature probe
- Overload protection fuses
- Secondary control modifiers
- 5" touch-screen display
- Six pluggable general-purpose relays
- Alarm relay for external alarm system
- VentGrid™ merged or traditional staged ventilation modes
- Corrosion-resistant, water-resistant, and fire-retardant enclosure
- Automatic temp-based control range

OPTIONS

- Humidity, ammonia, and carbon dioxide sensors
- Variable DC output module which adds four 0-10 VDC outputs
- Variable and fixed stage ventilation, curtains, heating, cooling equipment, and duty cycles are all offered as options

SPECIFICATIONS

- 5x Phasor 3K temperature sensor inputs
- 1x DOL-114 temperature and humidity sensor inputs
- 3x inputs for other compatible DOL sensors

WARRANTY

- 2-year limited warranty